

# Advantage

## FLOORING

A Division of Macdonald Polymers cc

TuffSeal™ refers to the physical shape and patented joining design of the tile. TuffCote™ refers to the in-house formulated & factory applied top surface coating of the tile.

All products in both the ULTRA and the EXTREME ranges are coated with TuffCote and are of the TuffSeal design. The difference between the ranges is in the material used in the tile base, and in the TuffCote™ formulation used.

### Properties: Chemical Resistance

Test Chemical	Test Duration	Test Result*
Ethanol (48%)	1h	5
NH <sub>4</sub> OH (10%)	1 min	5
Ammonium hydroxide	16h	5
Water (Deionised)	16h	5
Coffee (4%)	16h	5
Tea (1%)	5h	5
Red Wine	16h	5
Cola	2 min	5
Na <sub>2</sub> CO <sub>3</sub> (10%)	1h	5
Washing Soda	5h	5
Fatty Acid	16h	5
	5* = Best	0* = Worst

### Specifications & Facts

#### TuffSeal™

#### Tile Specifications

Tile Size	450x450mm
Tile Thickness	6.3mm
Hardness	88-91 Shore A
Tile Mass (nominal)	1.7kg
Coverage	4.9 tiles per m <sup>2</sup>
Area	0.2025 m <sup>2</sup> per tile
Base Material	Flexible PVC

#### Tuff 7

#### Tile Specifications

Tile Size	500x500mm
Tile Thickness	6.3mm
Hardness	88-91 Shore A
Tile Mass (nominal)	2.1kg
Coverage	4 tiles per m <sup>2</sup>
Area	0.25 m <sup>2</sup> per tile
Base Material	Flexible PVC